

AY-K25B

MIFARE Classic® EV1 Contactless
Smart Card Reader



This reliable unit provides the capability to read MIFARE Classic® EV1 smart card contactless cards with any standard access control system. With 7 programmable output formats, it will fit most existing system's needs and read the information required.

The AY-K25B is fully-potted, sealed and made of a rigid, UV resistant polycarbonate, which makes it highly suitable for outdoor use. With a maximum range of 4 cm (1.6 in.), it is a very simple, reliable and cost effective way to upgrade your system to the smart card standard.

GENERAL DESCRIPTION

The affordably priced AY-K25B reader is a contactless Serial ID Only reader that functions by reading MIFARE Classic EV1 ID Format Protocol via a variety of 13.56 MHz cards and tags. The adaptable AY-K25B is the answer for global companies seeking a uniform reader compatible with differing international mounting standards. Made of tough polycarbonate UV plastic and completely waterproof, the durable reader can withstand harsh weather conditions and tampering.

MAIN FEATURES

- Incorporates the ISO-14443A (MIFARE Classic EV1) ID Format Protocol
- Read range of up to 4 cm (1.6 in.)
- Multiple, programmable output formats including standard Wiegand 26-Bit
- Selectable LED control or buzzer control functions

- Made of tough polycarbonate plastic for improved performance in all weather conditions

PROFESSIONAL GRADE FEATURES

- Optical back tamper detection technology
- Bi-colored LED and LED control input
- Internal buzzer
- PC software and programming adapter (MD-08B) for easy configuration of the unit
- Weather-resistant

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

■ Operating Voltage Range	5–16 VDC, from a regulated power supply
■ Input Current	Standby: 49 mA @ 12 VDC Maximum: 67 mA @ 12 VDC
■ Tamper Output	Open collector, active low, max. sink current is 16 mA

OPERATIONAL SPECIFICATIONS

■ Inputs	Programmable LED control/buzzer control Input, N.O, Dry Contact
■ Indicators	Tri-colored LED indicators
■ Output Format	Programmable multi-format: Wiegand 26-Bit w/site code, Fixed 26-Bit, 32-Bit, 32-Bit Reversed, 34-Bit, 40-Bit, and Clock & Data
■ Built-In Proximity Reader	Max. read range: 4 cm (1.6 in.) Operating Frequency: 13.56 MHz Compatible Cards: MIFARE Classic EV1 Compatible ISO-14443A

ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	Water resistant, suitable for outdoor use (IP65 rated)
■ Operating Temperature Range	-31°C to 63°C (-25°F to 145°F)
■ Operating Humidity Range	0 to 95% (non-condensing)

PHYSICAL SPECIFICATIONS

■ Dimensions (H x W x D)	80 x 40 x 13 mm (3.2 x 1.6 x 0.5 in.)
■ Weight	54 g (1.9 oz)

SYSTEM COMPONENTS

The AY-K25B is compatible with a variety of Rosslare's controllers, as well as with many third-party systems, and is compatible with Rosslare's MIFARE Classic EV1 cards

PRODUCT WARRANTY

5-Year Limited Product Warranty

ABOUT ROSSLARE SECURITY

Rosslare Security Products manufactures and markets high-quality security products via its worldwide offices and channel partners. Since 1980, Rosslare has offered high-quality systems for enterprise, small business, and residential applications. With Rosslare, you receive the best of all worlds: world-class product engineering and design; professional customer service spanning the globe; and the quality and affordability of a vertically integrated and self-owned manufacturing facility. Our expansive product range features much more than access control solutions and guard patrol management systems; we also offer applications software – such as License Plate Recognition, Time & Attendance, and DVR/alarm integration.

www.rosslaresecurity.com

MIFARE® is a Trademark of NXP Semiconductors



ROSSLARE
SECURITY PRODUCTS
Experience the Difference